

Systems/C Utilities

Version 1.90

Systems/C Utilities
Version 1.90

Copyright © 2009 Dignus LLC, 8378 Six Forks Road Suite 203, Raleigh NC, 27615. World rights reserved. No part of this publication may be stored in a retrieval system, transmitted, or reproduced in any way, including but not limited to photocopy, photograph, magnetic or other record, without the prior agreement and written permission of the publisher.

This product includes software developed by the University of California, Berkeley and its contributors.

Copyright (c) 1990, 1993

The Regents of the University of California. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. All advertising materials mentioning features or use of this software must display the following acknowledgement:

This product includes software developed by the University of California, Berkeley and its contributors.

4. Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE REGENTS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE REGENTS OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

IBM, S/390, zSeries, OS/390, zOS, MVS, VM, CMS, HLASM, and High Level Assembler are registered trademarks of International Business Machines Corporation.

UNIX is a registered trademark in the United States and/or other countries licensed exclusively through X/Open Company Limited.

Microsoft, Windows, and Windows NT are trademarks of Microsoft Corporation in the United States and other countries.

Contents

How to use this book	1
Systems/C Utilities Overview	3
PLINK	5
Using PLINK	5
PLINK options	6
PLINK control statements	12
PLINK autocall processing	14
Running PLINK	16
Using PLINK to pre-link OpenEdition programs	17
Using PLINK to pre-link IBM C objects	17
Using PLINK to directly create load modules	18
Using PLINK to link programs on OS/390	19
DPDSLIB	21
Using DPDSLIB	21
Running DPDSLIB	21
DPDSLIB examples	21
DAR	23
Using DAR	23
Running DAR	23
DAR options	24
DAR examples	27
DRANLIB	29
Using DRANLIB	29
Running DRANLIB	29
DRANLIB options	30
DRANLIB examples	30
GOFF2XSD	31
Using GOFF2XSD	31
Running GOFF2XSD	32

DCCPC	33
Using DCCPC	33
Running DCCPC	33
DCCPC Options	34
DB2PPC	37
Using DB2PPC	37
Running DB2PPC	37
DB2PPC Options	39
D2S	43
Using D2S	43
D2S Options	45
ASCII/EBCDIC Translation Table	55

How to use this book

This book describes the utility programs provided with the Systems/C and Systems/C++ products and how to use these to create OS/390 programs.

For more information about Systems/C or Systems/C++, see the Systems/C or Systems/C++ manual.

For more information, contact Dignus, LLC at (919) 676-0847, or visit <http://www.dignus.com>.

Systems/C Utilities Overview

The Systems/C utilities are programs which help create and manage program creation and object libraries.

The utilities include:

- PLINK** The Systems/C pre-linker and linker. The pre-linker performs AUTOCALL name resolution to produce the object file that will be linked to become the final executable program, either in a PDS, PDSE or in the Hierarchical File System (HFS). On cross-platform hosts, **PLINK** can also create perform the final linking step locally, creating a TSO TRANSMIT file which contains the final OS/390 load module. This avoids any linking on the host.
- DPDSLIB** A utility which allows “autocalling” of long symbol names within a PDS on OS/390 or z/OS.
- DAR** The Systems/C archive librarian. DAR gathers together object files into a single entity which can be used for pre-linking.
- DRANLIB** The Systems/C ranlib utility. DRANLIB creates a symbol definition table in a DAR archive so that AUTOCALL resolution can find the defining instance of a symbol without depending on the DAR member name.
- GOFF2XSD** GOFF2XSD converts GOFF objects (generated by the IBM HLASM assembler) into XSD objects which the Systems/C pre-linker can employ.
- DCCPC** A CICS Command Processor for C source. Converts “EXEC CICS” commands into the appropriate C code to interface with the CICS run-time.
- DB2PPC** A DB2 Command Processor for C source. Converts “EXEC SQL” commands into the appropriate C code to interface with the DB2 run-time.
- D2S** A DSECT to `struct` converter. Converts DSECTs found in assembly ADATA files into C `struct` definitions.

PLINK

Using PLINK

PLINK gathers the input objects together, performing AUTOCALL resolution where appropriate, producing a single file which can then be processed by the IBM BINDER or IBM linker IEWL on older systems. Optionally **PLINK** can also perform the final linking step, producing a TSO TRANSMIT file containing the resulting load module.

Input to **PLINK** can be either object data sets, **DAR** archive libraries or control statements. **PLINK** supports GOFF, XOBJ and OBJ data set file formats. GOFF format object data sets must be fixed blocked with an LRECL=80.

When **PLINK** discovers an IBM LE object deck (an appropriately decorated XOBJ file), it performs the functions of the IBM LE pre-linker. Otherwise, as **PLINK** gathers objects, it performs the Systems/C pre-linking functions.

After performing pre-linking functions, if the *-b* option is specified, (indicating "binding") **PLINK** performs the functions of the IBM BINDER, resolving any remaining unresolved symbols, performing relocations and producing the resulting TSO TRANSMIT module which describes the load module. If the *-bonly* option is specified, no pre-linking functions are applied.

For Systems/C pre-linking, **PLINK** examines the defined symbols, looking for a Systems/C initialization script section. Furthermore, if the *-fnosname* option was specified on a **DCC** or **DCXX** command line, **PLINK** provides unique section names for the object. During this process, **PLINK** will produce warnings on discovering any duplicate definitions or duplicate section names.

At the end of the generated file, **PLINK** will append a section containing pointers to the located initialization script sections, which the Systems/C run-time library will use for re-entrant initialization. Also, if needed for C++, **PLINK** will generate the appropriate C++ constructor/destructor tables and place that in the resulting object.

If **PLINK** discovers any Dignus debugging information embedded in the object deck, **PLINK** will gather this information together and apply appropriate trans-

formations to make it ready to use by a debugger. **PLINK** will then generate a debugging information file that is associated with the eventual program.

On cross-platform hosts, **PLINK** may be employed to gather the objects together into one file for transferring to the mainframe for the final link step, or can perform the final linking itself, producing a load-module embedded in a TSO TRANSMIT file.

Unless the *-b* or *-bonly* option was specified, the output of **PLINK** is then intended to be processed by the IBM BINDER or linker to produce the executable load module.

PLINK options

PLINK supports the following options. Any remaining command-line parameters are treated as input object file names.

Also, on Windows, z/OS and OS/390 host platforms, **PLINK** supports the *-@filename* option. The contents of the specified file are inserted in the command line at the point where the *-@filename* appears. This provides a mechanism for specifying command lines which are greater than the operating system supports.

- ac=n* Specify the authorized program facility (APF) authorization code of the final executable, specified in the TSO transmit file, when the *-b* or *-bonly* option is enabled. The authorization code *n* must be an integer between 0 and 255. The default value is 0.
- allow_ref=name* The *-allow_ref* option defines a name that **PLINK** will not consider unresolved after all processing. After all AUTOCALL processing is performed, **PLINK** produces a list of unresolved references, and appropriately sets the return code. Symbol names specified via the *-allow_ref* option will not appear in this output, or affect the return code. Note, however, that *-allow_ref* does not provide a definition of the symbol, thus **PLINK** will continue to try and resolve any references to the *name* via normal AUTOCALL processing.
- amode=amode-setting* Specify the **AMODE** setting of the final executable when the *-b* or *-bonly* option is enabled. *amode-setting* can be either **any**, **min**, **24**, **31** or **64**.
- b* After performing normal pre-linking functions, **PLINK** will "bind" the objects, producing a load module. On cross-platform hosts, this causes **PLINK** to produce a TSO TRANSMIT file which can then be reinstated with the TSO RECEIVE command on the mainframe platform.
- blksize=N* Sets the block size of the resulting load module when the *-b* or *-bonly* options are specified. If *-blksize* is not specified, the default block size is 27998, the optimum block size for a 3390 device.

- `-bonly` Similar to `-b` except that normal pre-linking functions are not performed. Only the "binding" step is performed and a TSO TRANSMIT file is produced. This can be helpful if the object has been previously processed by **PLINK**.
- `-cmap[=file]` Causes **PLINK** to produce a report of the CSECT names assigned to input objects which were compiled with the `-fnosname` option. When `-fnosname` is used, **PLINK** assigns a unique name to the various sections produced by the compiler. This map can be helpful when referring back to particular objects based on the run-time section name. If `=file` is specified, the map is written to the specified file name, otherwise it is written to the `stdout` file stream.
- `-dbg=filename` Specifies the name of any **PLINK** produced debugging information file. If no `-dbg=` option is specified, **PLINK** uses a default name. The default name for the debugging information file on OS/390 and z/OS is `//DDN:SYSDBG`, on cross-platform hosts it is `p.dbg`.
- `-DD=NAME=template` Specify a "DD" definition to use for search for INCLUDE cards. The *NAME* specified is a DD-name that might appear as a PDS name on an INCLUDE card. The *template* specified is a search template which is expanded with the member name. The search template rules are the same as those used for AUTOCALL name searches. See the section on AUTOCALL searches for more information about template expansion. The section on INCLUDE card processing describes the use of the `-DD` option further.
- `-except=name1,name2,...` Specifies names that are exceptions to the "rename all" rule when the `-renameall` option is specified. The `-renameall` option renames all symbols except for names specified in the `-except` options. More than one name can be specified, each name is separated by commas. The `-except` option can be specified multiple times.
- `-fdaranycase` When **PLINK** performs autocall resolution using **DAR** archives, if there is no **DRANLIB**-generated symbol table, in the archive, **PLINK** uses the name of the member as the definition name. In this case, **PLINK** matches the reference to the **DAR** member name, much as PDS-based lookup would be performed in a traditional z/OS environment. By default, **PLINK** treats the member names and reference names as case-specific, matching only references with the exactly specified **DAR** archive member name. If the `-fdaranycase` option is specified, **PLINK** will ignore case differences on this match.

This can better approximate the PDS lookup that is performed on z/OS, where the names are all converted to upper-case by default.

`-fdllname=DLLNAME` When pre-linking IBM DLL objects, the `-fdllname` option specifies the name of the resulting DLL. It is similar to the `DLLNAME` option available on the IBM pre-linker.

If no `-fdllname` option is specified, **PLINK** uses the name `TEMPNAME`.

`-fmrc` Specifies that mainframe return code styles are to be used. This is the default on all platforms, but may change in the future. When `-fmrc` is enabled, **PLINK** returns a 0 for no warnings/errors, 4 if any warnings were generated and 8 or greater for errors.

`-fkeepweaktxt` The **Systems/C** and **Systems/C++** compilers allow for the multiple definition of `weak` functions. This feature is frequently employed by **Systems/C++** to accomplish automatic template instantiation.

PLINK handles duplicate `weak` function definitions by appropriately adjusting or deleting duplicate `ESD` entries and adjusting `RLD` relocation entries. Further **PLINK** actually removes the function code bytes from the resulting object file, creating a much smaller resulting object file for final linking.

There could be instances, however, where it would be desirable to retain the function code bytes in the resulting object. If `-fkeepweaktxt` is specified, **PLINK** will appropriately adjust `ESD` and `RLD` entries, but will not delete the duplicate function code. The code will remain in the resulting object, but will not be referenced in any fashion.

`-fmsgtostdout` Normally, **PLINK** writes error and warning messages to the `stderr` file stream. `-fmsgtostdout` causes the messages to be written to the `stdout` stream. This can be helpful on some Windows platforms that don't allow redirection of the `stderr` stream.

`-fnomrc` Specifies that UNIX (non-mainframe) return code styles are to be used. In a future release, this may become the default for cross-platform hosts (currently `-fmrc` is the default on all platforms.) When `-fnomrc` is enabled, **PLINK** returns a 0 even if any warnings were generated. If an error is generated, **PLINK** will return a non-zero value. This is helpful when incorporating **PLINK** into cross-platform build facilities (e.g. `make`) that expect a zero/non-zero return code.

`-fsysdefsd=file` Specify the name of the **PLINK**-generated definition file when pre-linking IBM DLL objects. This is the same as the `SYSDEFSD` DD specified on the IBM prelinker.

When pre-linking IBM DLL objects that export symbols **PLINK** will create the appropriate cards and write them to the named file.

If `-fsysdefsd` is not specified, **PLINK** writes the DLL definitions to a file name `"sysdefsd"`.

- lar** Add an archive file *ar* to the list of files to link. This option may be used any number of times. **PLINK** will search its *-L* path-list for occurrences of the file named `libar.a` for every *ar* specified.
- Lsearchdir** This command adds the path *searchdir* to the list of paths that **PLINK** will search for **DAR** archive libraries. This option may be used any number of times.
- map** Causes **PLINK** to produce a load-module offset map when the *-b* or *-bonly* option is enabled.
- noxmit** Normally, when the *-b* or *-bonly* options are specified, **PLINK** creates a TSO transmit file containing the resulting load module. The *-noxmit* option causes **PLINK** to simply write the "raw" load module records. When *-noxmit* is specified, the resulting file is not in TSO transmit format.
- Note that the load module records do not contain the module's starting offset and other information normally stored in the load module's PDS directory entry.
- ofile** The *-o* option specifies the name of the output *file*. On cross-platform hosts, **PLINK** writes to the file `p.out` by default; on OS/390 and z/OS **PLINK** writes to the file `//DDN:SYSMOD`.
- If the *-b* or *-bonly* options were specified, the output file is a fully realized load module in TSO TRANSMIT format.
- p** The *-p* option causes **PLINK** to process the incoming files, converting any long symbol entries to 8 characters. When a symbol entry longer than 8 characters is discovered, **PLINK** replaces it with a name of the form `STnnnnnnn`, where `nnnnnnnn` is a unique identifier given to the name. If the ultimate target of the load module is a PDS, and not a PDSE, then using the *-p* option will properly shorten the incoming names so the IBM binder will be able to properly link into the PDS. The **PLINK** output will display long names that are mapped to shorter ones.
- An *x* may be appended to the *-p* option. As well as converting long symbols to unique shorted names, specifying *-px* causes **PLINK** to convert XSD cards into ESD cards. Older versions of the IBM linker only handle ESD-type input. Specifying *-px* cause **PLINK** to generate output suitable for these older linkers.
- prefix=CCC** Typically, when renaming long names to unique short names, **PLINK** composes a name with a 3-character prefix (`@ST`) followed by 5 digits.
- The *-prefix* option can be used to specify an alternative prefix. Up to 3 letters can be specified. The first letter should be a character, or an '@' character, or a '#' character.

This can be helpful if the resulting objects are intended to be linked with another runtime environment. For example, the IBM runtime environment, since the IBM pre-linker also uses the prefix @ST.

`-prem` The `-prem` option causes **PLINK** to internally process DXD definitions and handle any CXD and Q-con relocations. The gathered DXD definitions are collectively called the *Pseudo Register Vector* or *PRV*. **PLINK** will gather DXD definitions into the PRV, assigning offsets to each. Then, any Q-cons which reference the elements of the PRV will be replaced with their offset. Any CXD relocations will be replaced with the total size of the PRV. **PLINK** will also produce a table indicating each DXD discovered, and its assigned offset. The PRV is used by the Dignus compilers to produce re-entrant code.

In order to properly produce the PRV table, all of the objects that contain DXDs, CXDs and Q-cons should be presented as input to **PLINK**.

The `-noprem` option can be used to disable this processing, if `-noprem` is specified, **PLINK** passes the DXD definitions and Q-con and CXD relocations through to the resulting object file.

Older IBM linkers, particularly for CMS and VSE, do not properly handle a PRV larger than 4K bytes. Thus, when generating code for these platform, `-prem` should be used.

The `-prem` is the default.

`-noprem` Disables **PLINK**'s processing of DXDs, CXDs and Q-cons. See the `-prem` option for more details.

`-r` Allow for re-running **PLINK** on the resulting object. If `-r` is specified, the result from **PLINK** will have all possible AUTOCALL operations performed, with no other processing. The resulting file can subsequently be reprocessed by **PLINK** to perform the other, normal processing. When `-r` is specified, the `-p` and `-px` options will be ignored. Also, any unresolved references will not be diagnosed, as it is assumed they will be resolved in a subsequent **PLINK** step.

`-refresh` Specify that the **REFRESHABLE** flag of the final executable should be set when the `-b` or `-bonly` option is enabled. `-refresh` may be abbreviated to `-refr`.

`-renameall` The `-renameall` option causes **PLINK** to rename all symbols in the generated object. This can be helpful when linking Systems/C DCALL modules with other runtime environments where the names might clash. For example, when linking a Systems/C DCALL'd object with IBM C/C++, or SAS C/C++.

The names chosen consist of a 3-character prefix, followed by a 5-digit number. By default, the 3-character prefix is @ST, but can be altered with the `-prefix` option.

When *-renameall* is specified, all symbols are renamed except for any specified via the *-except* option.

Thus, a typical approach would be to determine which symbols are meant to be visible to the calling program. Specify these names in the *-except* list, and specify the *-renameall* option. The resulting **PLINK**-generated object deck will have all of the symbols renamed except for the ones that need to be visible to any calling environment.

- rent* Specify that the RENT flag of the final executable should be set when the *-b* or *-bonly* option is enabled.
- reuse* Specify that the REUSE flag of the final executable should be set when the *-b* or *-bonly* option is enabled.

- rmode=rmode-setting* Specify the RMODE setting of the final executable when the *-b* or *-bonly* option is enabled. *rmode-setting* can be either **any** or **24**.

- showctl* Indicate that **PLINK** should provide information messages about any control cards encountered in the input. **PLINK** will produce messages of the form

plink: info: control card: text-of-card

where *text-of-card* is the text as it appeared on the input control card.

- syslmod=SSS* Specify the resulting output PDS name when the *-b* or *-bonly* options are enabled. The name *SSS* should completely specify the PDS name on the mainframe host. A member name can also optionally be specified.

- Stemplate* The *-S* option specifies a template which is expanded with the AUTOCALL reference name. Any **&m** and **&M** characters found in the template are replaced with the reference name, **&m** indicates that the lower-case version of the name should be used; **&M** indicates upper-case. On OS/390, **PLINK** has a default *-S* option of *-S//DDN:SYSLIB(&M)*.

- t* Normally, **PLINK** will issue diagnostic messages regarding duplicate definitions of symbols and sections. The *-t* option suppresses these messages. In any case, these duplicate definitions are not addressed by **PLINK** and are simply passed on to the IBM linker.

- u* The *-u* option causes **PLINK** to adjust the return code when unresolved references are discovered. Normally, after **PLINK** processing; if there remain any unresolved references, the return code will be 8. The *-u* option causes the return code to be 4 when unresolved references are encountered. This can be helpful if there are unresolved references at the **PLINK** step, which will be later resolved by the IBM BINDER.

- uu The *-uu* option operates the same as the *-u* option except that the return code will not be altered by any unresolved references. **PLINK** will continue to generate warnings regarding unresolved references, but they will not set the return code to 4.
- xref Causes **PLINK** to produce a load-module cross-reference listing when the *-b* or *-bonly* option is enabled.
- z The *-z* option is used to change **PLINK**'s processing of **DAR** archives. *-z* is followed by either `allextract` or `defaultextract`. In the default mode of operation, **PLINK** only extracts members of **DAR** archives which satisfy external references. If *-zallextract* is specified, **PLINK** will extract all members of subsequent archives found on the command line, essentially treating all the **DAR** archive members as primary input files. *-zdefaultextract* is used to return to the default extraction method.
- fquiet The *-fquiet* option causes `plink` to suppress all diagnostic output. Only error messages will be generated.

PLINK control statements

PLINK recognizes the `ARLIBRARY`, `IMPORT`, `INCLUDE INSERT`, and `RENAME` control statements in the input stream. When the *-b* or *-bonly* options are enabled, **PLINK** will also recognize `ENTRY` and `NAME` cards used for describing load modules.

If *-b* and *-bonly* are not specified, **PLINK** will copy all other control cards to the resulting output file. All such unrecognized control statements will be gathered together, and placed at the end of the **PLINK**-generated output.

`ARLIBRARY name` Adds name to the list of **DAR** archive libraries **PLINK** will examine to resolve external reference.

`ENTRY name` When *-b* or *-bonly* is enabled, this defines the resulting load module entry point. When the binding options are not enabled, this is copied to the resulting output file.

An entry point specified on an `ENTRY` card overrides any entry point specified on an `END` card in the input object.

If multiple `ENTRY` cards appear in the input, the last one discovered is used for specifying the entry point of the load module.

If no `ENTRY` card is specified, **PLINK** will use an entry point specified on an `END` card, or if no `END` cards specify an entry point, **PLINK** will use the first byte of the first control section.

`IMPORT type dll-name import-name` Used when pre-linking IBM DLL objects. The `IMPORT` card defines a datum/function that can be found in an

IBM DLL. *type* specifies the type of reference, either **DATA** or **CODE**. *dll-name* is the name of the DLL module that resolves the reference. *import-name* is the name of the DLL symbol.

IMPORT cards are generated by **PLINK** when pre-linking IBM DLL objects. These generated cards are then employed when the symbols in the DLL are to be referenced.

INCLUDE *name* Causes **PLINK** to include the object file *name* in its processing. On cross-platform hosts, **PLINK** handles **INCLUDE** cards of the form:

```
INCLUDE NAME( MEMBER)
```

in a manner designed to make transition from the mainframe easier.

PLINK will first look for a **DD** entry (from any **-DD** options) that specify the name *NAME*. If they are found, **PLINK** will expand the template specified in the **-DD** to search for the *MEMBER*.

If no **-DD** option specifies the *NAME*, then **PLINK** will consider *NAME* to be the name of an environment variable. This environment variable will be taken as a template value, just as if a **-DD** option had specified it.

If the *NAME* is not specified in the environment and is not specified by a **-DD** option, **PLINK** will attempt to open the file exactly as it appears on the **INCLUDE** code.

For example, on a Windows platform, if **PLINK** discovered the input card:

```
INCLUDE MYPDS(MYOBJ)
```

and the option **-DD=MYPDS=C:DIR1\&M.obj;C:DIR2\&M.obj** was specified, **PLINK** would first try to open the file named **C:\DIR1\MYOBJ.obj**. If that file was not available, **PLINK** would then try to open the file named **C:\DIR2\MYOBJ.obj**.

This approach allows for a mapping of **DD**-style concatenations to cross-platform systems; without changing the input to the pre-linker.

For more information about how search templates are expanded, see the section on **AUTOCALL** processing.

INSERT *symbol* Causes **PLINK** to add *symbol* as an external reference. If *symbol* has not been resolved when the primary input has been processed, **AUTOCALL** processing will attempt to resolve it. This card is also passed to the **PLINK** generated output.

NAME *name* When **-b** or **-bonly** is enabled, this defines the name of the resulting PDS member. When the binding options are not enabled, this card is copied to the resulting output file.

RENAME *longname shortname* Used to rename a symbol, providing a specific short-name for a long-named symbol. *longname* is the original symbol name; *shortname* is the resulting shortened name that will be used in the output object module. If the optional **SEARCH** keyword follows the *shortname* then the short name will be added to the list of unresolved references for **AUTOCALL** processing.

The **RENAME** card is only valid when performing IBM pre-linking functions. With normal Systems/C-style objects, the **RENAME** card will be copied to the output file.

PLINK autocall processing

PLINK will process **INCLUDE** cards and produce a list of external references. **PLINK** examines each object that participates in a program it will perform **AUTOCALL** processing to resolve any external references discovered in the primary input files.

During **AUTOCALL** processing, **PLINK** examines the list of unresolved external references, looking in the specified libraries for objects that will resolve the references. When such an object is found, it is examined for further references and for any re-entrant initialization sections. This process continues until all references are resolved, or determined to be unresolvable.

PLINK can employ either a direct file name approach to resolving external references, or take advantage of **DAR** archives, or any combination of these. **DAR** archives and *-S* specified templates are examined in the order they were discovered by **PLINK**, first on the **PLINK** command line and then in an **ARLIBRARY** control statements discovered in the input.

To search in locations specified by the *-S* option, **PLINK** simply expands the various specified templates with the reference name, and attempts to open the given file. If the open is successful, the file is processed, and the reference is considered resolved. If the file doesn't actually resolve the reference, **PLINK** will produce a warning message.

On hosts which have case-sensitive files systems (UNIX, OS/390 and z/OS), first an exact match of the reference name is tried; then either the upper-case or lower-case version is tried per the **&M** or **&m** characters in the template specification.

PLINK examines **DAR** archives by first looking for any **DRANLIB** generated symbol table member. If the symbol table member is present, **PLINK** uses the symbol table information to determine which member file resolves an external reference. Thus, **PLINK** is able to directly relate any file and its definitions. On hosts that support it, **PLINK** locks **DAR** archives as they are discovered. This prevents accidental changes to the **DAR** archive during **PLINK** processing. Because of this, a **DAR** archive should not be specified more than once on the **PLINK** command line.

When a symbol table member is not present, **PLINK** uses the name of the member in the archive to attempt to references, in a fashion similar to examining a PDS for a particular member. Note, however, that the file names in **DAR** archives are case-specific and thus **PLINK** uses a case-specific comparison in this case.

On OS/390 and z/OS, **PLINK** has two approaches to searching for PDS members which resolve a reference. If the **DPDSLIB** utility has created a table-of-contents file in the PDS, **PLINK** will use that file to determine which member resolves a reference. The table-of-contents file contains information regarding all of the symbols in each object file in the PDS. Thus, **PLINK** can use the table-of-contents to determine if an object resolves long names which cannot be represented in the PDS directory. If the table-of-contents file is not present in the PDS, **PLINK** will try and open the file name which is the same as the reference. See the section on **DPDSLIB** for more information regarding the table-of-contents member.

Running PLINK

On cross-hosted platforms (Windows and UNIX), **PLINK** is typically executed with the object files listed on the command line; and a *-S* option or library names to locate any required library objects.

For example, on a Windows platform the command:

```
plink -SC:\sysc\lib\objs_rent\&M prog.obj
```

will read the initial input file, `prog.obj` and examine the `C:\sysc\lib\objs_rent` directory for any AUTOCALL references. Because no *-o* option was specified, the resulting object file is written to the file `p.out`.

This command, on UNIX platforms:

```
plink t1.obj t2.obj libone.a -L../mylibs -ltwo
```

will read the two primary input objects `t1.obj` and `t2.obj`. It will try and resolve references from the **DAR** archive `libone.a` and then the second **DAR** archive `../mylibs/libtwo.a`.

On OS/390 and z/OS, when run from TSO or "batch" JCL, **PLINK** operates similar to the IBM pre-linker. The resulting gathered object is written to the file `//DDN:SYSMOD` unless otherwise specified. **PLINK** has a default library template of `-S//DDN:SYSLIB(&M)` which causes it to look in the SYSLIB PDS for autocall references, other input objects, *-S* library templates or **DAR** archives may be added in the PARMs option on the **PLINK** step. **PLINK** reads the file `//DDN:SYSIN` as the initial input file. Typically, this file contains INCLUDE cards to include the primary objects for the program. Other primary input files may be included in the PARMs for **PLINK**.

For example, the following JCL reads the object `INDD(PROG)` and uses `DIGNUS.LIBCR.OBJ` as the autocall library:

```
//PLINK EXEC PGM=PLINK
//STEPLIB DD DSN=Systems/C load library,DISP=SHR
//STDERR DD SYSOUT=A
//STDOUT DD SYSOUT=A
//SYSLIB DD DSN=DIGNUS.LIBCR.OBJ,DISP=SHR
//INDD DD DSN=mypds,DISP=SHR
//SYSIN DD *
INCLUDE INDD(PROG)
//SYSMOD DD DSN=myoutput.obj,DISP=NEW
```

Note that the **STDERR** and **STDOUT** DDs were specified for **PLINK**'s message output. Also, the **ARLIBRARY** control card could have been used to add additional **DAR** archive files for resolving external references.

When executed under the OpenEdition shell, **PLINK** operates as it does on any other UNIX platform.

Using **PLINK** to pre-link OpenEdition programs

Systems/C programs can be linked into the Hierarchical File System (HFS), producing a program that can be executed just as any other OpenEdition program.

To create an HFS load-module, the output from **PLINK** can be linked using the OpenEdition **cc** command. The **-e //** option should be added to the **cc** command to indicate that the entry-point is not the default Language Environment entry point expected by **cc**. The Systems/C runtime library will specify its own entry-point.

For example, to pre-link and link the object "myfunc.o" and produce the HFS load-module "myprog" under the OpenEdition shell (assuming /usr/local/dignus is the installation location), simply run **PLINK**:

```
plink -omyprog.o myfunc.o "-S/usr/local/dignus/objs_rent/&m"
```

then use the OpenEdition **cc** command:

```
cc -e // -omyprog myprog.o
```

to produce the myprog load-module. myprog can then be invoked as any other OpenEdition program.

For more information about creating OpenEdition programs with Systems/C, see the *Systems/C C Library* manual.

Using **PLINK** to pre-link IBM C objects

As well as pre-linking Systems/C and Systems/C++ modules, **PLINK** can perform the function of the IBM pre-linker for IBM C/C++ object modules.

PLINK automatically recognizes when the input contains IBM C/C++ object modules, and switches to "IBM pre-linking mode." It will then perform the same functions that the IBM pre-linker performs, using the same name-mapping algorithms, DLL processing and C++-specific processing.

When pre-linking IBM objects, **PLINK** will properly process the IBM **IMPORT** and **RENAME** input cards. The **-fdllname** and **-fsysdefsd** option specify the resulting DLL

name and name of the DLL definition file of any DLL exports are encountered in the input objects.

When in IBM pre-linking mode, the PLINK-generated listing will appear similar to the IBM pre-linker listing.

When converting from a mainframe environment to a cross environment; any PDS libraries used for pre-linking should be converted to **DAR** archives on the cross-platform host. Care should be taken ensure that AUTOCALL processing is consistent between the mainframe and cross-platform environments. If the PDS libraries have been processed by the IBM *Object Librarian*, then the equivalent **DAR** archive on the cross-platform host should be processed by the **DRANLIB** utility. When a PDS is processed by the IBM *Object Librarian*, a member named @@DC370\$ will be present. If that member is present, then the cross-platform **DAR** archive should be processed with the **DRANLIB** utility to ensure that proper "extended-name" AUTOCALLing will result. If the @@DC370\$ member is not in the PDS library, then **DRANLIB** should not be applied to the **DAR** archive, so that AUTOCALLing will use the member names.

If the resulting **DAR** archive is not processed by **DRANLIB**, then care should be taken to ensure that all of the names available in the PDS are also available in the **DAR** archive. This might include copying any PDS ALIASed members in the **DAR** archive so that all member names will be present. bf **DAR** archives have no "alias" facility, so a separate copy will be required.

Using PLINK to directly create load modules

PLINK can, on cross-platform hosts, optionally perform the final linking, or *binding* step and produce a load module. The load module will reside in a **PLINK**-created TSO TRANSMIT file suitable for receiving the resulting load-module with the TSO RECEIVE command.

When the *-b* or *-bonly* options are specified, **PLINK** will internally perform the final linking steps, or *binding*, and internally build the resulting load module. The *-b* option causes **PLINK** to perform its normal pre-linking steps, following by the binding step to create the load module. The *-bonly* option causes **PLINK** to only perform the binding process, skipping the normal **PLINK** pre-linking processing.

When binding is performed, the **PLINK** listing output will contain a load module map and symbol cross reference sections that are similar to those produced by the IBM linker.

After internally binding the load module, **PLINK** will create a TSO TRANSMIT file, which describes the resulting load module as if it resided on a 3390 direct-access device.

The resulting TSO TRANSMIT file should then be copied to a fixed-block data set,

with a logical record length of 80 bytes. Then, the RECEIVE command can be employed to realize the load module on an MVS, OS/390 or z/OS system.

The `-syslmod` option defines the name of the PDS on the mainframe platform. `-syslmod` can specify a PDS name and a member name. If a member name is not specified, **PLINK** will use a name specified on a NAME card in the input, or the name TEMPNAM0.

The `-blksize` option can be used to define the block size of the resulting PDS file. If no `-blksize` option is specified, **PLINK** uses a value of 27998, the optimum block size for a 3390 device.

For example, the following **PLINK** command will pre-link `obj1.obj`, `obj2.obj` and `obj3.obj`, producing the output TSO transmit file `prog.xmi`. The final location for the resulting load module will be in the PDS named "MY.PROGS.LOAD" in the member named "PROG".

```
plink -o prog.xmi -b -syslmod="MY.PROGS.LOAD(PROG)" obj1.obj
      obj2.obj obj3.obj
```

The `prog.xmi` file can then be copied to an FB-80 data set, and the RECEIVE command will produce the MY.PROGS.LOAD(PROG) load-module.

For more information about using the RECEIVE command, see the IBM publication *TSO/E Command Reference*.

Using PLINK to link programs on OS/390

Before execution, programs must be prepared, optionally using the Systems/C pre-linker, **PLINK**, then the IBM BINDER.

Systems/C provides two versions of the Systems/C C libraries, one for RENT programs and one for non-RENT programs. If you are using the Systems/C library, it is important to link with the appropriate version. If any source programs reference variables found in the Systems/C library (e.g. `errno`) and that program was compiled with the `-frent` option, then the re-entrant version of the Systems/C library should be used. Using the incorrect version of the library will cause strange run-time errors. The installation instructions for your particular host platform will detail where to find the correct Systems/C library. Normally the Systems/C library is specified as the last library to use for AUTOCALL resolution in the **PLINK** step. Furthermore, **PLINK** must be used for re-entrant programs that use the Systems/C library or to take advantage of **DAR** archive libraries for external reference resolution.

In the following example JCL, there are three objects to link together to form the resulting executable, `MAIN`, `SUB1`, and `SUB2`, representing a main module and two

supporting sub-modules. These are found in the PDS MY.PDS.OBJ. The resulting executable is written to MY.PDS.LOAD(MPROG).

```
//LINK JOB
//PLINK EXEC PGM=PLINK,REGION=2048K
//STEPLIB DD DSN=Systems/C load library,DISP=SHR
//STDOUT DD SYSOUT=*
//STDERR DD SYSOUT=*
//SYSLIB DD DSN=DIGNUS.LIBCR.OBJ,DISP=SHR
//SYSMOD DD DSN=&&PLKDD,UNIT=VIO,DISP=(NEW,PASS),
//      SPACE=(32000,(30,30)),
//      DCB=(RECFM=FB,LRECL=80,BLKSIZE=3200)
//INDD DD DSN=MYPDS.OBJ,DISP=SHR
//SYSIN DD *
INCLUDE INDD(MAIN)
INCLUDE INDD(SUB1)
INCLUDE INDD(SUB2)
//STDIN DD *
//LINK EXEC PGM=IEWL,REGION=2M,PARM=('LIST',
// 'MAP,XREF,LET',
// 'ALIASES=NO,UPCASE=NO,MSGLEVEL=4,EDIT=YES')
//SYSPRINT DD SYSOUT=*
//SYSUT1 DD UNIT=SYSDA,SPACE=(CYL,(1,1))
//SYSUT2 DD UNIT=SYSDA,SPACE=(CYL,(1,1))
```

First **PLINK** is invoked, specifying the inclusion of the three object modules and the Systems/C C reentrant library. This step could have been performed on a cross-platform host, running **PLINK** there. Then the IBM **BINDER** is invoked for final linking and generation of the resulting load module.

DPDSLIB

Using DPDSLIB

DPDSLIB is a utility provided on OS/390 and z/OS which allows autocall resolution of PDS members to account for long symbol names within the object members. Typically, when resolving names based on PDS members, **PLINK** attempts to resolve the reference by opening the PDS member with the same filename as the reference. This limits the length of external symbols to 8 characters. Also, **PLINK** converts the reference name to upper-case letters to find the PDS member, which may cause conflicts.

DPDSLIB will examine all of the objects in a PDS, creating a table-of-contents PDS member that describes each member in the PDS and the symbols it defines. It will then add this table-of-contents file to the PDS for **PLINK** to use later. Files in the PDS which are not GOFF, XSD or ESD format will be ignored. The name of the dictionary file in the PDS is **##SYMDEF**. In this regard, **DPDSLIB** performs a similar function to a PDS library as **DRANLIB** performs to a **DAR** archive.

Note that if members are added to, or changed in the PDS, the **DPDSLIB** program should be executed again to update the table-of-contents file.

Running DPDSLIB

DPDSLIB can be found in the Systems/C executable load module PDS for your installation, along with the other Systems/C programs. **DPDSLIB** may be executed either in TSO or with JCL as a batch program.

DPDSLIB has only one option, the name of the PDS to examine.

DPDSLIB examples

For example, if the PDS object library is named **USER.MY.LIB**, the following command under TSO would examine each of the members in **USER.MY.LIB** and create the **##SYMDEF** table-of-contents file.

```
DPDSLIB //DSN:USER.MY.LIB
```

Note that the specification of the PDS uses the Systems/C file naming conventions.

The following example demonstrates how to use **DPDSLIB** in a batch environment. In this example, the name of the PDS library to examine is given as the PARM value on the DPDSLIB EXEC statement.

```
...
//*
//* Execute DPDSLIB to add the table-of-contents
//* file to the PDS named in
//* the DD LIBRARY.
//*
//DPDSLIB EXEC PGM=DPDSLIB,
//          PARM='LIBRARY'
//STEPLIB DD DSN=Systems/C load library,DISP=SHR
//STDOUT  DD SYSOUT=*
//STDERR  DD SYSOUT=*
//LIBRARY DD DSN=PDS library name,DISP=SHR
```

DPDSLIB also supports multiple DSNs concatenated into a single DD definition. In this case, **DPDSLIB** will treat each DSN as its own library, as if **DPDSLIB** were executed on each DSN. For example, in the following JCL, the PDSs MY.PDS1, MY.PDS2 and MY.PDS3 will each be examined in turn, and a ##SYMDEF table-of-contents member will be added to each.

```
...
//*
//* Execute DPDSLIB to add the table-of-contents
//* file to the PDS named in
//* the DD LIBRARY. In this example the DD
//* refers to several DSNs
//*
//DPDSLIB EXEC PGM=DPDSLIB,
//          PARM='LIBRARY'
//STEPLIB DD DSN=Systems/C load library,DISP=SHR
//STDOUT  DD SYSOUT=*
//STDERR  DD SYSOUT=*
//LIBRARY DD DSN=MY.PDS1,DISP=SHR
//          DD DSN=MY.PDS2,DISP=SHR
//          DD DSN=MY.PDS3,DISP=SHR
```

DAR

Using DAR

The Systems/C archive utility, **DAR**, creates and maintains groups of files combined into an archive. Once an archive has been created, new files can be added and existing files can be extracted, deleted or replaced.

Files are named in the archive by a single component, i.e., if a file referenced by a path containing a slash (/) is archived on a UNIX platform, it will be named by the last component of that path. When matching paths listed on the command line against file names stored in the archive, only the last component of the path will be compared.

All informational and error messages use the path listed on the command line, if any was specified; otherwise the name in the archive is used. If multiple files in the archive have the same name, and paths are listed on the command line to “select” archive files for operation, only the *first* file with a matching name will be selected.

The normal use of **DAR** is for creation and maintenance of libraries suitable for use with the Systems/C pre-linker, **PLINK**, although it is not restricted to this purpose.

Running DAR

On UNIX and Windows cross-platform hosts, the **DAR** utility is located in the Systems/C installation directory, as **dar** on UNIX, or **DAR.EXE** for Windows. On OS/390, **DAR** is found in the Systems/C installation PDS, as the **DAR** member.

The **DAR** utility exits with a zero (0) return code on success, and greater-than zero (0) if an error occurs.

During processing, **DAR** requires several temporary files. On UNIX hosts, these will reside in `/tmp/dar.XXXXX`. On Windows hosts, these will be named `DAR#####.TMP` and will be located in the current directory. On OS/390, the files `SYSUT1-SYSUT5` may be employed (depending on the operation requested) and must be properly allocated.

The **DAR** utility accepts the following possible command lines formats:

```
DAR -d [-Tv] archive file ...
DAR -m [-Tv] archive file ...
DAR -m [-abiTv] position archive file ...
DAR -p [-Tv] archive [file ...]
DAR -q [-cTv] archive file ...
DAR -r [-cuTv] archive file ...
DAR -r [-abciuTv] position archive file ...
DAR -t [-Tv] archive [file ...]
DAR -x [-ouTv] archive [file ...]
```

The *archive* file name is provided after any options (possibly preceded by a *position* option, which names a member in the archive.) Following the archive file name is a list of member names, or *files* within the archive.

Also on Windows and OS/390 host platforms, **DAR** accepts a `-@filename` option. This option can be used to specify a command line larger than the host operating system supports. The contents of *filename* are examined and inserted in the command line argument list where the option appears.

DAR options

DAR options:

- `-a` A positioning modifier used with the options `-r` and `-m`. The files are entered or moved *after* the archive member *position*, which must be specified.
- `-b` A positioning modifier used with the options `-r` and `-m`. The files are entered or moved *before* the archive member *position*, which must be specified.
- `-c` Whenever an archive is created, an informational message to that effect is written to standard error. If the `-c` option is specified, **DAR** creates the archive silently.
- `-d` Delete the specified archive files.
- `-i` Identical to the `-b` option.
- `-m` Move the specified archive files within the archive. If one of the options `-a`, `-b` or `-i` is specified, the files are move before or after the *position* file in the archive. If none of these options are specified, the files are moved to the end of the archive.

- `-o` Set the access and modification times of extracted files to the modification time of the file when it was entered into the archive. This will fail if the user does not have sufficient authority for the operation, or the host file system does not support it.
- `-p` Write the contents of the specified files to the standard output. If no files are specified, the contents of all the files in the archive are written in the order they appear in the archive.
- `-q` (Quickly) append the specified files to the archive. If the archive does not exist a new archive file is created. This option can be much faster than the `-r` option, when creating a large archive piece-by-piece, as no checking is done to see if the files already exist in the archive.
- `-r` Replace or add the specified files to the archive. If the archive does not exist a new archive file is created. Files that replace existing files do not change the order of the files within the archive. New files are appended to the archive unless one of the options `-a -b` or `-i` is specified.
- `-T` Select and/or name archive members using only the first fifteen characters of the archive member or command line file name. The historic archive format had sixteen bytes for the name, but some historic archiver and loader implementations were unable to handle names that used the entire space. This means that file names that are not unique in their first fifteen characters can subsequently be confused. A warning message is printed to the standard error output if any file names are truncated.
- `-t` List the specified files in the order in which they appear in the archive, each on a separate line. If no files are specified, all files in the archive are listed.
- `-u` Update files. When used with the `-r` option, files in the archive will be replaced only if the disk file has a newer modification time than the file in the archive. When used with the `-x` option, files in the archive will be extracted only if the archive file has a newer modification time than the file on the disk. On those hosts file systems that don't support a modification time in the file system (i.e. OS/390 PDS members) this option produces an error message on the standard error output.
- `-v` Provide verbose output. When used with the `-d`, `-m`, `-q` or `-x` options, **DAR** gives a file-by-file description of the archive members. This description consists of three, white-space separated fields: the option letter, a dash ('-') and a file name. When used with the `-r` option, **DAR** displays the description as above but the initial letter is an "a" if the file is added to the archive and an "r" if the file replaces a file already in the archive.

When used with the `-p` option, the name of each printed file, enclosed in less-than (<) and greater-than (>) characters, is written to the standard output before the contents of the file; it is preceded by a single newline character, and followed by two newline characters.

When used with the `-t` option, **DAR** displays listing of information about the members of the archive. This listing is similar to the UNIX “`ls -l`” command, and consists of eight, white-space separated fields: the file permissions, the decimal user and group identifier numbers separated by a single slash (/), the file size (in bytes), the file modification time (in the date format “%b %e %H:%M %Y”), and the name of the file.

`-x` Extract the specified archive members into the files named by the command line arguments. If no members are specified, all the members of the archive are extracted into the current directory.

If the file does not exist, and the host file system supports it, it is created; if it does exist, the owner and group will be unchanged. The file access and modification times are the time of the extraction (but see the `-o` option for alternatives.) The file permissions will be set to those of the file when it was entered into the archive; this will fail if the user does not have sufficient authority for the operation, or the host file system does not support it.

DAR examples

The following JCL is an example of how to use DRANLIB on OS/390 or z/OS. Note the definition of the temporary file SYSUTO. This example creates the archive referenced in the ARCHIVE DD statement, using the three members MEM1, MEM2 and MEM3 from the OBJS DD.

```
...
//*
//* Execute DAR to create the archive named in
//* the DD ARCHIVE.
//*
//DAR EXEC PGM=DAR,REGION=2049K,
//          PARM='-@PARMS'
//STEPLIB DD DSN=Systems/C load library,DISP=SHR
//PARMS   DD *
-rv,ARCHIVE,OBJSMEM1,OBJSMEM2,OBJSMEM3
//STDOUT DD SYSOUT=*
//STDERR DD SYSOUT=*
//SYSUTO  DD UNIT=SYSDA,SPACE=(CYL,(5,1)),
//          BLKSIZE=80,LRECL=1,RECFM=FB
//ARCHIVE DD DSN=archive name,
//          DISP=(NEW,CATLG,DELETE),
//          SPACE=(CYL,(10,2),RLSE),
//          BLKSIZE=80,LRECL=1,RECFM=FB
//OBJSM   DD DSN= objs PDS,DISP=SHR
```

On UNIX or Windows platforms, the DAR program is invoked in a manner similar to the typical UNIX ar program. This example creates the archive named `libstuff.a`, from the three objects in the `objs` directory on a UNIX platform:

```
dar rv libstuff.a objs/mem1 objs/mem2 objs/mem3
```


DRANLIB

Using DRANLIB

The **DRANLIB** utility is used to create a table-of-contents member for **DAR** archive libraries. The **PLINK** pre-linker uses this table-of-contents member to resolve external references. This table is named “**...SYMDEF**” and is prepended to the archive. Files in the archive which are not GOFF, OBJ or XOBJ format object decks and symbols which are uninteresting to **PLINK** are ignored.

Running DRANLIB

On UNIX platforms, the **DRANLIB** utility is found in the Systems/C installation directory as the file **dranlib**. On Windows hosts, it is named **DRANLIB.EXE**. On OS/390 and z/OS, the **DRANLIB** utility is found in the Systems/C load module PDS as the **DRANLIB** member.

DRANLIB has the following command line:

```
DRANLIB [-t] file ...
```

where any number of **DAR** archive *files* may be specified.

DRANLIB requires temporary files to perform this operation. On UNIX platforms, these are found in **/tmp/dranlib.XXXXX**. On Windows platforms, the files **DRL#####.TMP** in the current directory will be used. On OS/390, the files **SYSUT1-SYSUT3** will be used and should be appropriately allocated.

DRANLIB returns with a return code of 0 on success, any non-zero return code indicates errors.

DRANLIB options

- `-t` Set the modification time of the generated `...SYMDEF` member in the archive. Some linkers (but not the Systems/C pre-linker **PLINK**) compare this time with the modification time of the archive to verify that the table is up-to-date with respect to the archive. If the modification time has been changed without any change to the archive (for example, by copying the archive), this option can be used to “touch” the modification time so that it appears the table is up-to-date. This is also useful on UNIX hosts after using the `-t` option of the `make` command. Note that this option is ineffective when running **DRANLIB** on OS/390 and z/OS.

DRANLIB examples

Some typical JCL for using DRANLIB on OS/390 might be:

```
//*
//* Execute DRANLIB to add the definition
//* symbol table to the archive named in
//* the DD ARCHIVE.
//*
//DRANLIB EXEC PGM=DRANLIB,REGION=2049K,
//          PARM='ARCHIVE'
//STEPLIB DD DSN=Systems/C load library,DISP=SHR
//STDOUT  DD SYSOUT=*
//STDERR  DD SYSOUT=*
//SYSUT0  DD UNIT=SYSDA,SPACE=(CYL,(5,1)),
//          BLKSIZE=80,LRECL=1,RECFM=FB
//SYSUT1  DD UNIT=SYSDA,SPACE=(CYL,(5,1)),
//          BLKSIZE=80,LRECL=1,RECFM=FB
//ARCHIVE DD DSN=archive name,DISP=(MOD)
```

On UNIX and Windows, the typical command for using DRANLIB is:

```
dranlib archive file name
```

For example, to add a symbol definition file to the archive `myarchive.a`, the command would be:

```
dranlib myarchive.a
```

GOFF2XSD

Using GOFF2XSD

GOFF2XSD is a program supplied with Systems/C which converts GOFF format object code to XSD format object code. The IBM HLASM generates GOFF format object code when the XOBJECT option is enabled. GOFF format, as well as XSD format, allows for identifiers which are longer than the 8-character limit imposed by the older ESD format. The Systems/C pre-linker **PLINK** can preprocess XSD object format files, converting them to ESD format which may be required by some older linkers. However, **PLINK** will not convert GOFF format directly to ESD format.

Typically, **GOFF2XSD** is used on an OS/390 or z/OS host, as part of the assembly step, but it is available and can be used on any Systems/C supported platform.

Running GOFF2XSD

GOFF2XSD accepts a *-o filename* option followed by the name of the input file as parameters. The *-o filename* option specifies where the output should be written. On OS/390 and z/OS, if *-o filename* is not specified, the output is written to the SYSOUT DD. Also, on OS/390, the output data set should be a fixed blocked file with 80 byte records (RECFM=FB,LRECL=80.)

On OS/390 and z/OS, if no input file is specified, **GOFF2XSD** reads from the SYSIN DD.

For example, if the HLASM step was named ASM, the **GOFF2XSD** SYSIN DD could refer back to the output of HLASM, and generate a SYSOUT object module suitable for inclusion by **PLINK** with the following JCL:

```
...
/**
/** Execute GOFF2XSD which translates the
/** HLASM-produced GOFF object into an
/** XSD-format object.
/**
/**GOFF2XSD EXEC PGM=GOFF2XSD,REGION=2049K
/**STEPLIB DD DSN=Systems/C load library,DISP=SHR
/**STDOUT DD SYSOUT=*
/**STDIN DD SYSOUT=*
/**SYSIN DD DSN=*.ASM.SYSLIN,DISP=(OLD,DELETE)
/**SYSOUT DD DSN=&&OBJ,UNIT=VIO,DISP=(NEW,PASS),
// SPACE=(32000,(30,30)),
// DCB=(RECFM=FB,LRECL=80,BLKSIZE=3200)
```

Note that the STDIN and STDOUT DDs are defined as well, **GOFF2XSD** writes any informative or error messages to those data sets.

On a cross-platform host, the following will translate the file named `goffin`, creating the XSD object file `xsdout`:

```
goff2xsd -o xsdout goffin
```

DCCPC

Using DCCPC

The Dignus CICS Command Processor, **DCCPC**, is used to translate C source code which uses **EXEC CICS** commands into normal C code prior to invoking **DCC**. This is especially useful in cross environments where IBM's translators cannot be used. For further information about CICS, see the IBM publication *CICS Transaction Server for z/OS: CICS Application Programming Reference* document number SC34-5994-02.

DCCPC implements all of commands from **CICS/ESA V4R1**, and many of the newer **CICS TS** commands as well.

Running DCCPC

On Windows and Unix, **DCCPC** is executed with a command line of the form

```
dccpc [options] [input file]
```

If no input file is specified, input is read from **stdin**.

When run on OS/390 and z/OS, options may be specified in the **PARM** statement. If no input file is specified, the **SYSIN DD** is used. Output defaults to **SYSPUNCH**, which would typically be used as input for **DCC** in the next step. Informational and error messages are output to **STDOUT** and **STDERR DD**s. The following JCL could be used on OS/390:

```
//DCCPC    JOB  
//DCCPC    EXEC PGM=DCCPC,PARM='options'  
//STEPLIB DD DSN=Systems/C load library,DISP=SHR  
//STDERR   DD SYSOUT=*  
//STDOUT   DD SYSOUT=*  
//SYSPUNCH DD SYSOUT=*  
//SYSIN    DD *  
          <C source>
```

DCCPC Options

Options for **DCCPC** are summarized in the table below.

-A	process assembly source
-C	process C source
-o <i>file</i>	place translated output in the file named <i>file</i>
-fdli / -fnodli	enable/disable support for EXEC DLI
-fgds / -fnogds	enable/disable support for GDS commands
-fsp / -fnosp	enable/disable support for System Programmer commands
-fcols= <i>n</i>	the output in C mode will be <i>n</i> columns
-fseq	the output in C mode will include sequence numbers
-fmrc / -fnomrc	enable/disable use of mainframe-style return code
-fflag= <i>code</i>	output only error messages of a certain priority
-fepilog / -fnoepilog	enable/disable use of DFHEIRET macro
-fprolog / -fnoprolog	enable/disable use of DFHEISTG, DFHEIEND, and DFHEIENT macros
-ferrlist / -fnoerrlist	enable/disable listing errors on <i>stderr</i>
-fcpp / -fnocpp	enable/disable C++ mode
-fexci / -fnoexci	enable/disable EXCI mode

The -A option (process assembly source)

The -A option tells **DCCPC** to process assembly source code.

The -C option (process C source)

The -C option tells **DCCPC** to process C source code instead of assembly code. -C is the default for **DCCPC**.

The -o *file* option (specify the name of the output file)

The -o *file* option specifies that the translated output should go to a file other than the default. On Windows and Unix systems, the default is `ccp.out`, while in OS/390 it is the `SYSPUNCH DD`.

The `-fdli` and `-fnodli` options (enable/disable EXEC DLI)

The `-fdli` option enables support for EXEC DLI statements as well as EXEC CICS statements.

The `-fgds` and `-fnogds` options (enable/disable GDS commands)

The `-fgds` option enables support for GDS commands (commands of the form EXEC CICS GDS ...). The default is `-fnogds`.

The `-fsp` and `-fnosp` options (enable/disable System Programmer commands)

The `-fsp` option enables support for System Programmer commands. The default is `-fnosp`.

The `-fcols=n` option (specify column width)

When processing C source code the `-fcols=n` option instructs **DCCPC** to use only *n* columns in its output. Assembly code is always limited to 72 columns with continuations.

The `-fseq` option (generate sequence numbers)

When processing C source code the `-fseq` option causes **DCCPC** to generate sequence numbers in the output. This implicitly sets `-fcols=72`. The sequence numbers appear in columns 73-80.

The `-fmrc` and `-fnomrc` options (enable/disable mainframe-style return codes)

The `-fmrc` option specifies that the translator should use mainframe-style return codes to indicate the exact error level reached. The `-fnomrc` option specifies that the translator should use Unix-style return codes that are either 0 (success) or 1 (errors). On OS/390 `-fmrc` is the default, while on cross-platform hosts `-fnomrc` is the default.

The `-fflag=code` option (output only error messages of a certain priority)

The `-fflag=code` option specifies that only error messages at least as severe than `code` should be displayed. Valid values for `code` are **I** for informational messages, **W** for warnings, **E** for errors, and **S** for severe errors. The default is `-fflag=I`.

The `-fepilog` and `-fnoepilog` options (enable/disable use of DFHEIRET macro)

The `-fnoepilog` option specifies that the DFHEIRET macro should not be invoked in the translated assembly source. This option is needed to make the CICS RETURN command effective. The default is `-fepilog`.

The `-fprolog` and `-fnoprolog` options (enable/disable use of DFHEISTG, DFHEIEND and DFHEIENT macros)

The `-fnoprolog` option specifies that the DFHEISTG, DFHEIEND and DFHEIENT macros should not be invoked in the translated assembly source. These macros define local storage that is allocated a program start up. The default is `-fprolog`.

The `-ferrlist` and `-fnoerrlist` options (enable/disable listing of errors on `stderr`)

The `-ferrlist` option enables the listing of errors on `stderr`. The `-fnoerrlist` option specifies that errors should just be listed as comments in the translated output file and is the default.

The `-fcpp` and `-fnocpp` options (enable/disable C++ mode)

The `-fcpp` option can be used with the `-C` option to use C++ instead of C for input and output. `-fcpp` has no effect if `-C` is not specified.

The `-fexci` and `-fnoexci` options (enable/disable EXCI mode)

The `-fexci` option instructs **DCCPC** to run in EXternal Call Interface mode, for processing files which contain only a special form of the EXEC CICS LINK command. When run in EXCI mode, no other commands will be translated. Outside of EXCI mode, this special form of the EXEC CICS LINK command is unavailable.

DB2PPC

Using DB2PPC

The Dignus DB2 Command Processor, **DB2PPC**, is used to translate C source code which uses **EXEC SQL** commands into normal C code and a DBRM file prior to invoking **DCC**. This is especially useful in cross environments where IBM's translators cannot be used. For further information about DB2, see the IBM publication *DB2 UDB for z/OS V8 SQL Reference* document number SC18-7426-03.

Running DB2PPC

On Windows and Unix, **DB2PPC** is executed with a command line of the form

```
db2ppc [options] [input file]
```

If no input file is specified, input is read from **stdin** and C output is generated on **stdout** and DBRM output is generated in **out.dbrm**.

If an input file is specified but no output files are specified then the output file names are based off of the input file name. For example, if the input is **file.c**, then the translated C output will be in **file_pp.c** and the DBRM will be in **file.dbrm**.

When run on OS/390 and z/OS, options may be specified in the **PARM** statement. If no input file is specified, the **SYSIN** DD is used. C output defaults to **SYSCIN**, which would typically be used as input for **DCC** in the next step. **DBRM** output defaults to the **DBRMLIB** DD. Informational and error messages are output to **STDOUT** and **STDERR** DDs. The following JCL could be used on OS/390:

```
//DB2PPC   JOB
//DB2PPC   EXEC PGM=DB2PPC,PARM='options'
//STEPLIB  DD DSN=Systems/C load library,DISP=SHR
//STDERR   DD SYSOUT=*
//STDOUT   DD SYSOUT=*
//SYSCIN   DD C output dataset
//DBRMLIB  DD DBRM output dataset
//SYSIN    DD *
           <C source>
```

DB2PPC Options

Options for **DB2PPC** are summarized in the table below.

-A / -C	process assembly / C source
-d <i>file</i>	place DBRM output in the file named <i>file</i>
-I <i>path</i>	search for include files in <i>path</i>
-o <i>file</i>	place translated output in the file named <i>file</i>
-fmrc / -fnomrc	enable/disable use of mainframe-style return code
-fnewfun / -fnonewfun	enable/disable support for V8 NEWFUN mode
-fattach= <i>mode</i>	specify attachment mode
-fconnect=1 / -fconnect=2	specify type for CONNECT statement
-ffloat=ieee / -ffloat=s390	specify type of floating point variables
-fpadtstr / -fnopadtstr	enable/disable padding of NUL-terminated strings
-fsql=all / -fsql=db2	specify which SQL dialect to accept
-fstdsql	use SQL rules for statements
-fversion= <i>ver</i>	set the version field in the DBRM header
-fcpp	enable C++ mode
-fonepass / -ftwopass	select one- or two-pass preprocessor operation
-ffold / -fnofold	enable/disable folding identifiers to uppercase
-fprog= <i>name</i>	override the DBRM "program name" header field
-fuser= <i>name</i>	override the DBRM "user name" header field

The -A and -C options (process assembly / C source)

The -A option tells **DB2PPC** to process assembly source code. It implies *-ffold* and *-ftwopass* options, so if you wish to override these options then you must specify (i.e.) *-fonepass* at a point after -A on the command line.

The -C option tells **DB2PPC** to process C source code. The default is to process C source code.

The `-d file` option (place DBRM output in the file named *file*)

When `-d file` is specified, **DB2PPC** generates DBRM output in the specified file. If `-d` is not specified, then the output filename is determined from the input filename with the extension replaced by `.dbrm`. If no input filename is specified then output is placed in `out.dbrm` or the DBRMLIB DD.

The `-I path` option (search for include files in *path*)

Any paths specified with `-I path` will be searched (in the order given) when resolving EXEC SQL INCLUDE statements. The current directory (".") is always searched.

If you wish to include a file with an extension, please enclose the file name in quotes, as in:

```
EXEC SQL INCLUDE "file.c"
```

The `-o file` option (place translated output in the file named *file*)

When `-o file` is specified, **DB2PPC** generates translated C output in the specified file. If `-o` is not specified, then the output filename is determined from the input filename with the extension replaced by `.pp.c`. If no input filename is specified then output is on **stdout** or the SYSCIN DD.

The `-fmrc / -fnomrc` option (enable/disable use of mainframe-style return code)

The `-fmrc` option specifies that the translator should use mainframe-style return codes to indicate the exact error level reached. The `-fnomrc` option specifies that the translator should use Unix-style return codes that are either 0 (success) or 1 (errors). On OS/390 `-fmrc` is the default, while on cross-platform hosts `-fnomrc` is the default.

The `-fnewfun / -fnonewfun` option (enable/disable support for V8 NEWFUN mode)

By default, **DB2PPC** supports the **NEWFUN** mode of DB2 V8 and produces DBRM output using UTF-8 character encoding and uses some extended structures. If `-fnonewfun` is specified, however, then output compatible with DB2 V7 is produced, using EBCDIC encoding for the DBRM output.

The `-fattach=mode` option (specify attachment mode)

The `-fattach=mode` option is used to specify the function for **DB2PPC** to use to attach to the DB2 server. There are three valid settings:

<code>tso</code>	Use DSNHLI (default).
<code>caf</code>	Use DSNHLI2.
<code>rrsaf</code>	Use DSNHLIR.

The `-fconnect=1` / `-fconnect=2` option (specify type for CONNECT statement)

If `-fconnect=1` is specified then **DB2PPC** generates the type 1 form of the `CONNECT` statement. By default, the type 2 form is generated.

The `-ffloat=ieee` / `-ffloat=s390` option (specify type of floating point variables)

If `-ffloat=ieee` is specified then **DB2PPC** notes that floating point host variables are in IEEE format instead of IBM's HFP format. The default is `-ffloat=s390`.

The `-fpadntstr` / `-fnopadntstr` option (enable/disable padding of NUL-terminated strings)

The `-fpadntstr` causes **DB2PPC** to note that NUL-terminated strings should be padded out to their full field length. The default is `-fnopadntstr`, in which case a NUL is used to indicate the end of data in the string regardless of length.

The `-fsql=all` / `-fsql=db2` option (specify which SQL dialect to accept)

The `-fsql=all` option tells **DB2PPC** to accept all valid SQL syntax, even if it is not necessarily valid DB2 syntax. The default is `-fsql=db2`.

The `-fstdsql` option (use SQL rules for statements)

The `-fstdsql` option changes the `SQLCA` area to allow SQL rules for statements.

The `-fversion=ver` option (set the version field in the DBRM header)

The `-fversion=ver` option causes the specified string to be placed in the DBRM extended version header. The string is also placed in the C variable `SQLVERS.VERSSTR`.

The `-fcpp` option (enable C++ mode)

The `-fcpp` option causes the preprocessed output to be compatible with C++ compilers. The default is to output code compatible with C compilers.

The `-fonepass` / `-ftwopass` options (select one- or two-pass preprocessor operation)

The `-fonepass` option is the default and causes **DB2PP** to process the source in a single linear pass, so all declarations must come before references. The `-ftwopass` option causes **DB2PP** to process the source file in two passes, first reading declarations, and the second pass generating output.

The `-ffold` / `-fnofold` options (enable/disable folding identifiers to uppercase)

When `-ffold` is specified, all non-string identifiers will be converted to uppercase. `-fnofold` is the default option for C source. `-ffold` is the default option for ASM source.

The `-fprog=name` option (override the DBRM "program name" header field)

The **DBRM** output file has a "program name" header field which must match the member name of the DBRM when it is bound. Otherwise the **DB2 BIND** step will produce a "consistency error." By default, the program name is derived from the DBRM output filename. If this does not match the actual names used on MVS, you may use `-fprog=name` to override the default.

The `-fuser=name` option (override the DBRM "user name" header field)

The **DBRM** output file has a "user name" header field. By default, your user name is determined using the value of the `USER` environment variable, but you can override it with the `-fuser=name` option.

D2S

Using D2S

D2S is used to convert assembly DSECTs into C `struct` definitions. **D2S** examines ADATA information generated by the Systems/ASM assembler, **DASM**, or by IBM's HLASM assembler. **D2S** extracts DSECT information from the ADATA file generating a C structure definition suitable for use in a C or C++ header (".h") file.

For example, if the EXAMPLE DSECT was defined as in the following assembly source:

```
EXAMPLE DSECT
NEXT    DS   A           Address of next element
NAME    DS   CL30        Customer name
ID      DS   F           Customer ID number
                          END
```

then **D2S** would convert that DSECT into the following C structure:

```
struct example {
    void * __ptr31 next;           /* Address of next element */
    unsigned char name[30];       /* Customer name */
    char        __filler0[2];
    int         id;               /* Customer ID number */
};
```

Notice that **D2S** preserved the original comments, and has inserted filler in order to ensure the fields match exactly with the original DSECT definition.

For more information on how to use **DASM** to generate the ADATA information required by **D2S**, refer to the *Systems/ASM Assembler* manual. For more information on how to use IBM's HLASM, refer to IBM *HLASM V1R4 Programmer's Guide* document number SC26-4941-03.

A simple UNIX or Windows **DASM** command to generate **ADATA** information in the file **adata** would be

```
dasm -A=adata example.asm
```

On Windows and Unix, **D2S** is executed with a command line of the form

```
d2s [options] input file
```

When run on OS/390 or z/OS, options may be specified in the **PARM** statement. If no input file is specified, the **SYSIN** DD is used. Output defaults to the **EDCDSECT** DD. Informational and error messages are output to **STDOUT** and **STDERR** DDs. The following JCL could be used on OS/390:

```
//D2S      JOB
//D2S      EXEC PGM=D2S,PARM=' options'
//STEPLIB DD DSN=Systems/C load library,DISP=SHR
//STDERR   DD SYSOUT=*
//STDOUT   DD SYSOUT=*
//EDCDSECT DD SYSOUT=*
//SYSIN    DD DSN=ADATA(FOO),DISP=SHR
```

D2S Options

<code>-help</code>	display usage information
<code>-s <i>sect_name</i></code>	specify section (DSECT) to convert
<code>-com / -xcom</code>	enable/disable passing through comments
<code>-anon / -xanon</code>	enable/disable the use of anonymous substructures/unions
<code>-def / -xdef</code>	enable/disable <code>#define</code> directives for substructures/unions
<code>-equ=<i>opt</i> / -xequ</code>	control how EQU symbols are converted
<code>-style=<i>kind</i></code>	control the style of the generated C structures
<code>-in=<i>count</i> / -xin</code>	control indentation
<code>-lc / -xlc</code>	enable/disable converting names to lower case
<code>-elc / -xelc</code>	enable/disable converting EQU names to lower case
<code>-ll=<i>count</i> / -xll</code>	set a maximum output line length
<code>-pp / -xpp</code>	include preprocessor directives to prevent duplicate definitions
<code>-seq / -xseq</code>	enable/disable sequence numbers on the output
<code>-unique=<i>str</i> / -xunique</code>	specify a unique string for building labels
<code>-out=<i>filename</i></code>	specify a different output filename
<code>-char=<i>type</i></code>	specify the type to be generated for DS C members
<code>-prefixmap=<i>old,new</i></code>	specify a string mapping to be performed on member names

The `-help` option (display usage information)

This option causes **D2S** to output basic usage information on the `stdout` stream.

The `-s sect_name` option (specify section to convert)

The `-s` parameter specifies that **D2S** should convert the DSECT named *sect_name*. If the `-s` parameter is not specified then all DSECTs will be converted.

The `-com` and `-xcom` options (pass through comments)

If `-com` is specified then **D2S** will copy comments found in the `ADATA` information into the generated C source. `-xcom`, causes these comments to be discarded instead. The default is `-com`.

The `-anon` and `-xanon` options (control the use of anonymous substructures/unions)

Systems/C and Systems/C++ offer an `-fanonstruct` option that provides the capability for `union` and `struct` members of another `struct` to be unnamed (and the members of the anonymous structures and unions members are then considered to be members of the enclosing structure). `-anon` is the default and causes **D2S** to generate C code which uses anonymous substructures and unions. Consider the following DSECT example:

```
TEST DSECT
A    DS OF
A1   DS CL1
A2   DS CL1
A3   DS CL1
A4   DS CL1
```

With `-xanon` it converts to the following C structure:

```
struct test {
    union {
        int          a;
        struct {
            char      a1;
            char      a2;
            char      a3;
            char      a4;
        } __struct0;
    } __union0;
};
```

Whereas `-anon` causes the following C structure to be generated:

```
struct test {
    union {
        int          a;
        struct {
            char      a1;
            char      a2;
            char      a3;
            char      a4;
        };
    };
};
```

The `-def` and `-xdef` options (control `#define` directives)

The `-def` and `-xdef` options control the generation of `#define` directives for sub-structures/unions. `-def` is only useful if `-xanon` is also specified, in which case the following lines would be generated for the `-xanon` example:

```
#define a __union0.a
#define a1 __union0.__struct0.a1
#define a2 __union0.__struct0.a2
#define a3 __union0.__struct0.a3
#define a4 __union0.__struct0.a4
```

`-xdef` is the default.

The `-equ=opt` and `-xequ` options (control EQU conversion)

The `-xequ` option is the default and instructs **D2S** to discard EQU symbols. There are four possible values for *opt*:

- `def` Output `#defines` for EQU symbols.
- `bit` Output bitfields for EQU symbols, using the value of the EQU as a bit mask.
- `bit1` Like `bit`, except using the length as a bit mask.
- `mixed` Like `bit`, except symbols which do not work as bitfield masks are output as `#defines` rather than discarded.

For example, consider the DSECT:

```
TEST DSECT
BF DS CL2
FLG EQU 4
FLGS EQU 3
```

If *-equ=def* is specified then the following C structure is generated:

```
struct test {
    unsigned char  bf[2];

    #define flg 4
    #define flgs 3

};
```

If *-equ=bit* is specified then the following C structure is generated instead:

```
struct test {
    /* bitfield for bf: */
    unsigned int  __filler0 : 13;
    unsigned int  flg : 1;
    unsigned int  flgs : 2;

};
```

For `-equ=bitl` consider the following DSECT:

```
TEST DSECT
A    DS CL4
B    DS CL3
BF   DS CL2
FLG  EQU A
FLGS EQU B
```

which is converted to:

```
struct test {
    unsigned char  a[4];
    unsigned char  b[3];
    /* bitfield for bf: */
    unsigned int   __filler0 : 13;
    unsigned int   flg : 1;
    unsigned int   flgs : 2;
};
```

The `-style=kind` options (control the style of the generated C structures)

The `-style=` option provides control over the style of C structures **D2S** produces.

The valid styles are *fold*, *nest* and *raw*.

When the *raw* style is specified, **D2S** does not attempt to reorganize the generated structures in any fashion. Although this will result in a faithful reproduction of the assembly language DSECT, the C source can be unpleasant to read if the DSECT is at all complicated. There will be many `union` and `struct` fields with appropriate filler bytes defined to ensure everything is placed at the correct offset. Also, when `-style=raw` is specified, the structure will be "flat" with no nested sub-structures.

When the *fold* style is specified, **D2S** will reorganize structures to try to remove unnecessary filler fields. This can make the structure quite different in order from the original assembly language source.

When the *nest* style is specified, **D2S** will again attempt to reorganize the defined structure to remove unnecessary filler fields. However, it will attempt to recognize common assembly-language constructs that indicate one element of the DSECT is a "sub-structure" of the others. In doing so, it will retain the same order of definition in the generated C structure as was discovered in the original assembly language source. The result of the conversion when `-style=nest` is specified are typically more "C like" while retaining the intent of the original source.

For example, given the following DSECT:

```
TEST DSECT
A   DS F   OFFSET 0
B   DS F   OFFSET 4
    ORG B
C   DS F   OFFSET 4
D   DS F   OFFSET 8
    ORG D
E   DS F   OFFSET 8
    END
```

if `-style=raw` is specified then the following C structure will be generated:

```
struct test {
    union {
        struct {
            int          a;          /* OFFSET 0 */
            int          b;          /* OFFSET 4 */
        };
        struct {
            char         __filler0[4];
            int          c;          /* OFFSET 4 */
            int          d;          /* OFFSET 8 */
        };
        struct {
            char         __filler1[8];
            int          e;          /* OFFSET 8 */
        };
    };
};
```

when `-style=fold` is specified, the following C structure will be generated:

```
struct test {
    int          a;                /* OFFSET 0 */
    union {
        struct {
            int    b;                /* OFFSET 4 */
            int    e;                /* OFFSET 8 */
        };
        struct {
            int    c;                /* OFFSET 4 */
            int    d;                /* OFFSET 8 */
        };
    };
};
```

and, when `-style=nest` is specified, the following, more "nested" C structure will be generated:

```
struct test {
    int          a;                /* OFFSET 0 */
    union {
        int      b;                /* OFFSET 4 */
        struct {
            int    c;                /* OFFSET 4 */
            union {
                int    d;            /* OFFSET 8 */
                int    e;            /* OFFSET 8 */
            };
        };
    };
};
```

The `-in=count` and `-xin` options (control indentation)

If `-in=count` is specified then `count` spaces will be used in nested members of C structures. `-xin` is equivalent to `-in=0`. The default is `-in=2`.

The `-lc` and `-xlc` options (control case conversion)

If `-lc` (the default) is specified then all symbol names (except for EQU names) are converted to lower case by **D2S**. `-xlc` specifies that the names are to remain in their original form.

The `-elc` and `-xelc` options (control EQU case conversion)

If `-elc` (the default) is specified then the names of EQU symbols are converted to lower case by **D2S**. `-xelc` specifies that the EQU names are to remain in their original form. `-xelc` may be desirable if `-equ=def` is used, as C programmers often prefer that `#define` constants have uppercase names.

The `-ll=count` and `-xll` options (control output line length)

The `-ll=count` option specifies that the output lines are to be no wider than *count* columns. `-xll` removes this limit and is the default.

The `-pp` and `-xpp` options (control guard preprocessor directives)

When `-pp` is specified, **D2S** will generate preprocessor directives to guard against duplicate definitions of the same structure. `-xpp` is the default and specifies that no such directives are to be generated.

The directives for an example structure would look like:

```
#ifndef example__
#define example__

struct example {
    ...
};

#endif /* example__ */
```

The `-seq` and `-xseq` options (control sequence number output)

The `-seq` option causes **D2S** to output sequence numbers in columns 73-80, implying `-ll=72`. The default is `-xseq` which specifies that no sequence numbers are to be output.

The `-unique=str` and `-xunique` options (control label building)

When **D2S** encounters a symbol with characters which C does not accept, it replaces them according to the following table:

Character	Replacement value
@	<i>str a str</i>
#	<i>str n str</i>
\$	<i>str d str</i>

The default for *str* is the empty string, which can be specified with *-xunique*. If *-unique=_* were specified then the label X\$Y would be converted to the C symbol X.d.Y.

The *-out=filename* option (specify output filename)

The *-out=filename* option specifies that the C output should be directed to *filename*. If no *-out=filename* is specified then on Windows or Unix “.h” is appended to the name of the input file and used as the output file. On MVS //DDN:EDCDSECT is the default.

The *-char=type* option (specify the type to be generated for DS C members)

By default when a DSECT member defined as DS C is encountered, a C member with type **unsigned char** is generated. However, sometimes it may be necessary to use a different character type for compatibility with other declarations, especially in C++. If *-char=char* is specified then members of type **char** are generated. If *-char=signed* is specified then members of type **signed char** are generated. If *-char=unsigned* is specified then members of type **unsigned char** are generated.

For some cases such as oddly-sized members of a non-character type (i.e., DS FL5), an **unsigned char** member will be generated regardless of the setting of the *-char=type* option. These members are essentially placeholders and do not properly represent the meaning of the underlying type.

The *-prefixmap=old,new* option (specify a string mapping to be performed on member names)

Since DSECT members are all in the global namespace, many assembly programmers use a common prefix for all members of the same DSECT. The *-prefixmap=old,new* option allows you to replace the prefix string with a new string. If the *new* string is not provided, i.e., *-prefixmap=str*, then any prefix of *str* on a member name is stripped. The *-prefixmap* option may be specified more than once, to specify several different prefixes. The prefix mapping is applied before any other translation on the member names (such as lowercasing, or @, #, \$ translation), so your *old* string must exactly match the prefix used in the assembly source.

ASCII/EBCDIC Translation Table

The Dignus utilities use the following tables to translate characters between ASCII and EBCDIC. These tables represent the mapping of the IBM Code Page 1047 to ISO LATIN-1.

ASCII to EBCDIC

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0	00	01	02	03	37	2D	2E	2F	16	05	15	0B	0C	0D	0E	0F
1	10	11	12	13	3C	3D	32	26	18	19	3F	27	1C	1D	1E	1F
2	40	5A	7F	7B	5B	6C	50	7D	4D	5D	5C	4E	6B	60	4B	61
3	F0	F1	F2	F3	F4	F5	F6	F7	F8	F9	7A	5E	4C	7E	6E	6F
4	7C	C1	C2	C3	C4	C5	C6	C7	C8	C9	D1	D2	D3	D4	D5	D6
5	D7	D8	D9	E2	E3	E4	E5	E6	E7	E8	E9	AD	E0	BD	5F	6D
6	79	81	82	83	84	85	86	87	88	89	91	92	93	94	95	96
7	97	98	99	A2	A3	A4	A5	A6	A7	A8	A9	C0	4F	D0	A1	07
8	20	21	22	23	24	25	06	17	28	29	2A	2B	2C	09	0A	1B
9	30	31	1A	33	34	35	36	08	38	39	3A	3B	04	14	3E	FF
A	41	AA	4A	B1	9F	B2	6A	B5	BB	B4	9A	8A	B0	CA	AF	BC
B	90	8F	EA	FA	BE	A0	B6	B3	9D	DA	9B	8B	B7	B8	B9	AB
C	64	65	62	66	63	67	9E	68	74	71	72	73	78	75	76	77
D	AC	69	ED	EE	EB	EF	EC	BF	80	FD	FE	FB	FC	BA	AE	59
E	44	45	42	46	43	47	9C	48	54	51	52	53	58	55	56	57
F	8C	49	CD	CE	CB	CF	CC	E1	70	DD	DE	DB	DC	8D	8E	DF

EBCDIC to ASCII

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
0	00	01	02	03	9C	09	86	7F	97	8D	8E	0B	0C	0D	0E	0F
1	10	11	12	13	9D	0A	08	87	18	19	92	8F	1C	1D	1E	1F
2	80	81	82	83	84	85	17	1B	88	89	8A	8B	8C	05	06	07
3	90	91	16	93	94	95	96	04	98	99	9A	9B	14	15	9E	1A
4	20	A0	E2	E4	E0	E1	E3	E5	E7	F1	A2	2E	3C	28	2B	7C
5	26	E9	EA	EB	E8	ED	EE	EF	EC	DF	21	24	2A	29	3B	5E
6	2D	2F	C2	C4	C0	C1	C3	C5	C7	D1	A6	2C	25	5F	3E	3F
7	F8	C9	CA	CB	C8	CD	CE	CF	CC	60	3A	23	40	27	3D	22
8	D8	61	62	63	64	65	66	67	68	69	AB	BB	F0	FD	FE	B1
9	B0	6A	6B	6C	6D	6E	6F	70	71	72	AA	BA	E6	B8	C6	A4
A	B5	7E	73	74	75	76	77	78	79	7A	A1	BF	D0	5B	DE	AE
B	AC	A3	A5	B7	A9	A7	B6	BC	BD	BE	DD	A8	AF	5D	B4	D7
C	7B	41	42	43	44	45	46	47	48	49	AD	F4	F6	F2	F3	F5
D	7D	4A	4B	4C	4D	4E	4F	50	51	52	B9	FB	FC	F9	FA	FF
E	5C	F7	53	54	55	56	57	58	59	5A	B2	D4	D6	D2	D3	D5
F	30	31	32	33	34	35	36	37	38	39	B3	DB	DC	D9	DA	9F